



Hydraulic Implement Routine Maintenance

Proper servicing is key to the long life of any attachment. With careful inspection and routine maintenance, you can avoid costly downtime and repair. Below are items that require routine maintenance for proper functionality and longevity of your hydraulic implement. Maintenance should be conducted every 10hrs or before starting a large project with extensive use of the attachment.

⚠ WARNING: *Hydraulic fluid under high pressure will penetrate the skin or eyes, causing a serious injury. Wear protective gloves and safety glasses or goggles when working with hydraulic systems. Use a piece of cardboard or wood rather than hands when searching for leaks. If an accident occurs, seek immediate emergency medical care.*

- Check all bolts and pins to ensure they are secured.*
- Lubricate all grease zerks with multi-purpose grease.*
- Clean all loose debris from all moving parts and pinch points.
- Check hitch fitment to ensure debris has not loosened the hitch connection.
- Check hydraulic fittings, hoses, and cylinders for any damage.
- Replace worn, damaged, or missing parts before operating.*
- Check that your tractor's hydraulic reservoir is free of contaminants and at the proper level.
- Clean your hydraulic fitting to ensure no contaminants enter your hydraulic system.

If you have any questions regarding your implement's maintenance or replacement parts, don't hesitate to contact our sales team!

Email: sales@homesteadimplements.com

Phone: 833-625-0635

**Consult your owner's manuals for grease points, torque ratings, and replacement parts.*