

BUILT TOUGH BUILT TO

6-WAY BACK BLADE



Homestead Implements Pinnacle Series Back Blade

Technical Specification

Model Numbers	HI-P-ABB-60	HI-P-ABB-72	HI-P-ABB-84
Working Width	60" (1.52m)	72" (1.83m)	84" (2.13m)
Height and Length	37.51"(0.95 m) over all height and 45.595"(1.16m) over all length	39.03"(1.00 m) over all height and 46.58"(1.18m) over all length	
Weight	253 lbs. (114.76 kg)	310 lbs. (140.61 kg)	334 lbs. (151.5 kg)
Blade Offset	18" (45.7cm) left or right		
Blade Angle	Up to 45° Clockwise and Counter Clockwise		
Moldboard Tilt Angle	Up to 15° Clockwise and Counter Clockwise		
Lift Mechanism	Lower lift arms 3/8" Plate mounted on 3" x 3" x 3/16" (7.6cm x 7.6cm x 4.8mm) Tube and upper lift arms 3/8" Plate mounted on 3/8" A-Frame	Lower lift arms 3/8" Plate mounted on 4" x 3" x 3/16" (10.16cm x 7.6cm x 4.8mm) Tube and upper lift arms 3/8" Plate mounted on 3/8" A-Frame	
Moldboard	A-36 grade moldboard - 14" (35.6cm) Height and 1/4"(6.3mm) Thick		
Number of Cutting Blades	1 blade		
Cutting Blade Properties and Size	High carbon steel, heat treated cutting edges 1/2" x 6" (12.7mm x 152.4mm)		
Cutting Blade Function	Reversible and Replaceable		
Maximum H.P. Rating	55 Horsepower (41 kw)		
3-Point Hitch Type	Category-1 Quick-Hitch & iMatch Compatible	Category-1 & Category-2 Quick-Hitch & iMatch Compatible	