

# SUB-COMPACT GRAPPLE



## Homestead Implements Independence Series Grapple for Sub-Compact Tractors

### Technical Specification

<b>Model Numbers</b>	<b>HI-I-SCG-54</b>
<b>Weight</b>	190 lbs (86.2 kg)
<b>Overall Width</b>	54" (1.37 m)
<b>Closed Height</b>	30" (0.76 m)
<b>Jaw Opening</b>	29" (0.74 m)
<b>Number of Teeth</b>	7 Bottom & 6 Top
<b>Teeth Spacing</b>	8 23/32" (22.1 cm) on bottom teeth and 9 1/2" (24.1 cm) on the top teeth
<b>Tooth Thickness and Material</b>	1/4" (6.35 mm) HARDOX® 450
<b>Working Length of Teeth</b>	8 7/8" (22.5cm)
<b>Hydraulic Cylinder</b>	2" (5.1cm) x 4"(10.2cm) x 1 1/8"(2.8cm) Rod, 2 Nos.
<b>Maximum Pressure Rating</b>	2500 PSI
<b>Hose Size and Connector</b>	3/8" (9.5mm) ID with JIC flare fitting
<b>Hose Size</b>	1/2" (12.7mm) ID with NPT threading
<b>Hose Pressure Rating</b>	6000 PSI
<b>Hitch Attachment</b>	Universal Quick-Attach (SSQA)
<b>Recommended Tractor Specifications</b>	Up to 30 HP & less than 1,000 lbs lift capacity